

	TBD 2024 production. Subject to material availability. "The January 2018 implementation of the new EPA Green House Gas Regulation, has been put off indefinitely. If at some future date the regulation is reinstated, it may require certain options to improve fuel efficiency and reduce emissions that are not included in this specification. Among these are low rolling resistance tires, aerodynamic devices, tire monitoring or inflation systems, and weight reduction. Orders that do not meet the requirements are subject to change orders and any cost increases that result."			
	SUBJECT TO Material Cost Review and SURCHARGE 90 days prior to QTR of production		Original Release 10/29/24	
	Workorder TM601030 SN TM601055 - TM601129		Revised 11/11/24	
				Weight 13650
Quantity	55 units Model Year 2026	option		
Body Type	VXP	VXP		
Width	102-5/16"	std		
Length	53' 0" (52' 6" inside with swing doors, 52' 5" with OHD)	std		
Height	13' 6" (110" inside)	std		
Door Opening	110" tall x 99" wide	std		
Door Type	1/2" Composite pp white galvanized inner and outer panels	std		
Door Holdbacks	Rubber bumper on bottom hinge, chain and loop on door with hook recessed into base rail.	std		
Grabhandle	None	std		
Inside Width	101" scuff to scuff (101-1/4" panel to panel)	VXP		
	47-3/16" with ultra high strength approach plate and 1/4" 67K bottom plate. Approach plate extends up front of trailer 2-1/4" creating approximately 3/8" thick fifthwheel impact area. Galvanized front lip.			
Upper Coupler Height		std		
King Pin Location	36"	std		
Tire / Wheel Size	295/75R22.5 / 8.25 x 22.5	std		
Tire Make	Cooper PRO Series LHT or Yokohama BE 109L FACTORY CHOICE radial. Smartway approved	new std		
Tire Inflation System	Hendrickson TireMaax PRO	option		18
Wheel Type	2HH disc powder coated white	std		
Hubo on Bracket	None	std		
Outboard Cast Drums	Yes, machine balanced. Long studs.	std		
Number of Axles	Two	std		
Axle Make	As provided with suspension. Extended life brake lining. Tapered spindle.	std		
Wheel Seals	Stemco Guardian HP seals.	std		
Bearing Lubrication	HEARTLAND #0 SYN-POLY SEMI-FLUID GREASE	new std		
Spindle Nut	ZIP-Torq	new std		
Hubcaps	Stemco vented. Stemco Platinum Performance Plus System (5 year limited warranty)	std		
Suspension	Hendrickson HKANT40K with SureLok and QuikDraw	option		
	49" spread 216" slide rails (72" to 174" slide range) (Note: Vanguard standard Holland slide rails specified with 6" center hole spacing with 1.56" hole diameter)			
Tandem Slide		std		
Brake Size & Type	16.5" x 7" Air "S" - Cam	std		
Air Lines	3/8" diameter front to rear	std		
ABS	Bendix 2S-1M with SR-5 spring brake release valve. (Haldex cannot supply)	option		
Slack Adjusters	WABCO automatic (5 year limited warranty)	new std		
Brake Chambers	Haldex Gold Seal (4 year limited warranty). Includes brake stroke indicator.	std		
Landing Gear	Jost Magnum A450.G3.17.73 Galvanized bracing. 103" from KP. (10 yr warranty)	new std		
Landing Gear Crank Roadside	Yes	std		
Tire Carrier	No	std		
Crossmembers	4" I-Beam 12" O/C. 7 crossmembers over LG.	std		
	Aluminum squeeze rivets. 9mil black vinyl tape installed full height of base rail between crossmembers and base rail for electrolysis barrier.			
X-member to Base Rail Attachment		std		
Floor	1-3/8" Rockland with Floor Saver 100% Oak with three 5/16" screws per board	std		
Threshold Plate	Heavy duty galvanized unitized forklift package and rear sill last 27" of trailer	std		
Scuff Band Sides	6" x 18ga 80KSI corrugated steel above integral aluminum totaling 12" scuff.	VXP		
Scuff Band Front	None	std		
Internal Bulkhead	10ga x 12" smooth steel attached directly to front wall posts	std		
Sidewall Liner	N/A	VXP		
Nose Liner	1/2" plywood full height with close out at bottom	std		
Ceiling Liner	None	std		
Side Panels	VXP Composite Plate	VXP		
Side Posts	Series "A" logistics posts on 48" centers.	VXP		
Front Wall Panels	PPW Aluminum with 1/8" mill finish aluminum radius panels.	std		
Front Wall Posts	FIVE 2" deep hat section posts	std		
Roof Bows	1" deep galvanized steel anti-sag on 16" / 24" centers	std		
Roof Material	.040 Aluminum pre-bonded to bows prior to installation	std		
Rear Frame Color	GALVANIZED	std		
Midcam Lock	No	std		
Lock Rods per Door	One	std		
Hinges per Door	Five	std		
Rubber Dock Bumpers	One pair (4-hole) recessed between lights	std		
	Reinforced for Dock-Lock operation. GALVANIZED. (outboard verticals). Vanguard has earned the Insurance Institute for Highway Safety's TOUGHGUARD award for having a rear guard that helps to prevent underride of a midsize car traveling 35 MPH in three test modes — full-width, 50 percent overlap and 30 percent overlap. ALL RIG parts are bolt on.			
Rear Impact Guard (RIG)		std		
Flaps Mtd. to Slider	Yes 24" x 27-1/2" white antispray with Vanguard logo.	std		
	Optronics LED (Limited Lifetime Warranty) All Locations including license. Canada and California legal lights. Five lights rear header. Front and rear header lights with multi-function. GloLights at rear and mid-turn. Lower lights attached with aluminum closed end pop rivet for anti theft.			
Sealed Beam Lights		std		
Wiring Harness	Phillips split wiring harness with internal ground. (10 year warranty)	std		
7-Way Receptacle	Phillips Q-Box (split pin without circuit breakers). Non corrosive housing.	std		
	Phillips anodized with screens, non swivel type offset to roadside. REAR ACCESS MOUNT.			
Gladhands		new std		
Registration Holder	James King 300	option	11/11/2024	
Manifest box	Aluminum (8.5" x 13") located driverside front wall	option	11/11/2024	
Tracking System	NONE	std	2/19/2025	
Tracking System	None	option	11/11/2024	

Vents	Louvered style one located upper roadside front, one located lower curbside rear door.	option	11/11/2024	10
Logistic Track	None	std		
Side Skirts	EVolution (Model E-1930T-EVO) by Transtex CARB Bin III (1AER00109 white)	option		137
External Rub Rail	None	std		
Undercoating	Pre-undercoated crossmembers and floor. Holland suspensions have Black Armour coating. Hendrickson suspensions have black soft coat. Slide rails are sprayed with undercoat and inside of coupler is sprayed.	std		
Customer Markings	NONE	std	2/19/2025	